

MEISTER INTERNATIONAL LLC
OEM & Utility Standoff Insulators

Meister Intl Part Number	Dimensions - Inches		Insert Thread Each End	Minimum Creep - inches	Strike Inches	Voltage (kV) Rating	BIL kV	Strength Rating in lbs.		
	Diameter	Height						Cantilever 5/8" above top	Tension	Compression
MI-70100	2	2 1/2	3/8 #16	3	2 1/2	2.5	45	550	1375	6500
MI-70105	2	3 1/2	3/8 #16	4 1/2	3 1/2	5	75	350	1400	6500
MI-70110	2	5 1/8	3/8 #16	7	5 1/8	8.7	95	225	1600	6500
MI-70125	2 1/2	3	3/8 #16	4 1/2	3	5	60	425	1775	8000
MI-70130	2 1/2	4	3/8 #16	7	4	8.7	75	425	1775	8000
MI-70140	2 1/2	6	3/8 #16	10 1/2	6	15	110	225	1850	8000
MI-70150	3 1/8	2 5/8	1/2 #13	4	2 5/8	5	60	525	1800	10000
MI-70155	3 1/8	3 3/8	3/8 #16	5	3 3/8	5	60	515	1925	10000
MI-70160	3 1/8	3 3/8	1/2 #13	5	3 3/8	5	60	515	1925	10000
MI-70165	3 1/8	4	1/2 #13	6	4	7.5	75	510	2000	10000
MI-70169	3 1/8	5	3/8 #16	7 1/4	5	8.7	95	275	1725	10000
MI-70170	3 1/8	5	1/2 #13	7 1/4	5	8.7	95	275	1725	10000
MI-70174	3 1/8	6	3/8 #16	10 5/8	6	15	110	260	1600	8000
MI-70175	3 1/8	6	3/8 #16	10 5/8	6	15	110	260	1600	8700
MI-70176	3 1/8	6	1/2 #13	10 5/8	6	15	110	260	1600	8000
MI-70190	3 1/2	3 1/2	1/2 #13	6 1/4	3 1/2	7.5	75	700	2400	12000
MI-70200	3 1/2	3 1/4	1/2 #13	4	3 1/4	5	60	800	2750	15000
MI-70205	4	3 15/16	1/2 #13	7 5/8	3 15/16	8.7	75	750	2350	20000
MI-70210	4	4 5/8	1/2 #13	9 1/4	4 5/8	8.7	95	575	1900	20000
MI-70214	4	6	3/8 #16	12 3/8	6	15	110	375	2000	20000
MI-70215	4	6	1/2 #13	12 3/8	6	15	110	375	2000	20000

MEISTER INTERNATIONAL LLC Tel: 513-923-2712
P.O. Box 338 Fax: 513-923-1978
Ross, OH 45061 Email: sales@meisterintl.com
 web: www.meisterintl.com